

PRZEDMIAR

NAZWA INWESTYCJI : Modernizacja zagospodarowania terenu na rzecz poprawy zapewnienia dostępności osobom ze szczególnymi potrzebami
ADRES INWESTYCJI : os. Władysława IV nr 1-5, Swarzędz
INWESTOR : Spółdzielnia Mieszkaniowa w Swarzędzu
ADRES INWESTORA : 62-020 Swarzędz, ul. Kwaśniewskiego 1.
BRANŻA : elektryczna
DATA OPRACOWANIA : 28.04.2023

WYKONAWCA :

INWESTOR :

Data opracowania
28.04.2023

Data zatwierdzenia

PRZEDMIAR

Lp.	Podstawa	Nr spec. techn.	Opis i wyliczenia	j.m.	Poszcz.	Razem
INSTALACJA CCTV						
1	KNR AL-01 0501-02 analogia		Dostawa i montaż elementów systemu telewizji użytkowej - kamera zewnętrzna AXIS P1467-LE wraz z osprzętem : Kamera - AXIS P1467-LE - Compact outdoor, NEMA 4x, IP66 and IK10-read 5MP resolution, day/night, fixed bullet camera with Deep Learning Processing Unit (DLPU), Support for ForensicWDR and Lightfinder 2.0 and OptimizedIR, Varifocal 2.8-8 mmP-Iris lens with remote zoom and focus, Multiple, individually configurable H.264/H with Zipstream and Motion JPEG, 5MP at 25/30, AXIS Zipstream technology for reduced bandwidth and storage needs, AXIS Object Analytics, Video motion detection, shock detection and active tampering alarm. Barrel distortion correction, deogging and scene profiles. Audio in and supervised I/O port, microSD memory card slot for local storage. MQTT Support, AXIS Edge Vault for added cyber security. OptimizedIR, a power-efficient IR LED technology . Integrated bracket for easy mounting on wall and ceiling. Power by IEEE 802.3af/802.3at Type 1 Class 3 and 10-28V DC power with redundancy, Operating conditions -40°C to 60°C (-40°F to 140°F), includes removable sunshield mounting bracket Torx L-keys and IP66/67 - rated cable glands 4	kpl. kpl.	 4,00	
					RAZEM	4,00
2	KNR AL-01 0501-02 analogia		Dostawa i montaż elementów systemu telewizji użytkowej - kamera zewnętrzna AXIS P1377-LE wraz z osprzętem : Kamera - AXIS P1377-LE - Outdoor, NEMA 4x, IP66/67 and IK10-read 5MP resolution, day/night, fixed box camera providing Forensic WDR and Lightfinder technology. OptimizedIR, a power - efficient IR LED technology covering 50 meters (130feet), Includes an IR corrected varifocal 2.8-8 mm F1.2 P-Iris lens with remote zoom and focus. Camera also supports CS-mount Ds-Iris lenses and i-CS lenses for remote installation zoom and focus. Multiple, individually configurable H.264, H.265 and Motion JPEG, 5MP at 50/60 fps, AXIS Zipstream technology for reduced bandwidth and storage needs, Video motion detection, shock detection, active tampering alarm and open casing intrusion switch, Corridor format, Barrel distortion correction, de-fogging and electronic image stabilization , Scene profiles. Two-way audio , audio detection with optimal analog or digital microphone, supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optimal local video storage. Serial port for RS-422/485 communication. Operating in -40°C to 60°C , PoE+ class 4 or 12-28VDC input. Support 2	kpl. kpl.	 2,00	
					RAZEM	2,00